# Redefine your limits with P3020 Prime



#### **Specification**

•	
Payload (kg)	30
Reach (mm)	2,030
Tool Speed (m/s)	Over 1
Joint - Range (°)	±[360 125 160 360 360]
Joint - Speed (°/sec.)	[100 80 80 200 360]
Repeatability (mm)	± 0.1
Weight (kg)	83
Protection Rating	IP54
Temperature (°C)	0~45
Cable (m)	6

**Doosan Robotics** 

#### **Features**

### Stack a 30kg(66 lbs) weight up to 2m(78.8 in) high!\*

The most powerful payload and reach

Boasting an impressive **30kg** payload and a **2,030 mm** reach **Optimal specs** for **unbeatable palletizing performance** 

DOOSAN

2030mm

\*Including tool weight (standard vacuum gripper, 3-5kg)
Using a standard base, without using a lift

## Maximize productivity in the most cost-effective way

**Reduced cost and cycle time** due to superior capabilities and performance

Palletize to 2m (78.8 in) high without use of a lift\*

Low power consumption (307W)

- Equivalent to a **household refrigerator**
- **Approximately 25% lower** than similar cobot in the same class (400W)

\*Using only the standard base

The Pioneer of high payload collaborative robots

Exceed limits and rediscover possibilities with the new P3020

#### The new standard in palletizing

5-axis design optimized for palletizing, offering greater stability and faster performance than ever before

Works perfectly with **any standard pallet**, including those from Korea, Europe, and the United States



